

## IKO carrara Quadra 6 m

01567566

### Description:

Waterproofing membrane composed of elastomer (SBS) bitumen with fire-retardant properties and a polyester-glass combination inlay. The upper surface is finished with white titanium dioxide granulate (SRI 82) and the vapour pressure-distributing lower surface is protected by a thermofusible film. This top layer can be applied in a single- or multi-layer system.

### Installation

Installation: partially torched-on.

### Composition

|                      |  |
|----------------------|--|
| Type of bitumen      | Elastomeric  |
| Upper surface finish | White granulate  |
| Inlay                | Polyester-glass combination 250 g/m <sup>2</sup> (trilaminate) |
| Lower surface finish | Quadra profile with thermofusible film                         |

### Technical characteristics:

|  |              |
|--|--------------|
| Tensile strength L (EN 12311-1 MDV N/50 mm +/- 20%)            | 1000         |
| Tensile strength T (EN 12311-1 MDV N/50 mm +/- 20%)            | 900          |
| Elongation L (EN 12311-1 MDV % +/- 15% abs.)                   | 50           |
| Elongation B (EN 12311-1 MDV % +/- 15% abs.)                   | 55           |
| Nail tear resistance(EN 12310-1 MDV N Only MF)                 | ≥ 150        |
| Flexibility at low temperature (EN 1109 MLV °C Surface/Bottom) | ≤ -25        |
| Flow temperature (EN 1110)                                     | ≥ 110        |
| Shear resistance (EN 12317-1 MDV N/50 mm)                      | ≥ 500        |
| Dimensional stability (EN 1107-1 MLV)                          | ≤ 0.3        |
| Fire resistance  | Broof(t1-t3) |
| Vapour diffusion resistance (μd)                               | NPD          |
| Root resistant (EN 13948)                                      | -            |

### Packaging:

|                          |                            |
|--------------------------|----------------------------|
| Nominal thickness (mm)   | 4,0                        |
| Thickness tolerance (mm) | +/- 0,2                    |
| Length (m)               | 6                          |
| Width (m)                | 1                          |
| Width of overlap (cm)    | 10,0                       |
| Weight per roll(kg)      | +/- 38                     |
| Number of rolls / pallet | 25                         |
| Type of pallet           | 1 x 1,2 m guarantee pallet |

### Certificates:

- ATG 2996
- CTG 500
- Production ISO 9001 & 14001

IKO hereby certifies that this construction product complies with the provisions of the following European Directive(s) if installed in accordance with the system directions and installation rules set out in the documentation:

- Council Directive 89/106/EEC on Construction Products
- EN 13707

FPC certificate obtained from SGS Notified Body, registered under registration number 0958.

Certificate number: 0958-CPR-2009/1.

