

Activator

Description:

Ready-to-use adhesive, that is used as a primer in order to improve the adhesion of self-adhesive roof membranes.

IKO pro Activator can also be used as a contact adhesive for bitumen roof felt with a lower surface protected by a macro-perforated thermofusible film.

Use:

Improves the adhesion to the substrate of both self-adhesive roof membranes and of bitumen roof felt with a lower surface protected by a macro-perforated thermofusible film.

Packaging:

4,5kg metal tin (item number 30451900)

Storage:

12 months in the hermetically sealed packaging, when stored in a dry and cool place.

Partly used containers may be resealed and used again after correct storage.

To avoid the risk of spillage, always store and transport in a secure upright position.

Colour:

Black

Application:

The air temperature and the product temperature should be between 5°C and 25°C.

The substrate needs to be sound, clean and free from grease and non-adhering particles.

Stir firmly before application, don't dilute.

Apply a thin film with an adapted spray system based on air-pressure with a minimum pressure of 4 to 5 bar or with a spray gun with adjustable spray field and adjustable airflow rate. Alternatively, use a paintbrush or roller for small surfaces and details.

Allow the solvents to evaporate from the IKOpro Activator layer for 5 to 10 minutes (at 10°C).

Apply the membrane to the prepared substrate and press down firmly.

Consumption rate:

150-250 g/m²

Cleaning of tools:

IKO pro Gun Cleaner

Certificates:

Production ISO 9001 & 14001



The technical information regarding the application of liquid waterproofing products supplied by IKO is provided in good faith on the basis of IKO's current know-how and experience, and assumes that these products will be used in accordance with the above-mentioned recommendations, under normal circumstances, and provided that these products were stored and handled in the correct manner. The above-mentioned information is only intended to inform the user about the various properties and/or recommendations and can in no way be considered as a guarantee with regard to the merchantability and suitability for a specific purpose in view of the continuously changing environmental factors, including the specific conditions at the building site, the use of different materials and substrates, etc. As a result, and with the exception of binding legal stipulations to the contrary, IKO cannot be held liable on the basis of the provided information, and any other written recommendations and/or advice. Please contact IKO if you have any doubts regarding the processing, the end use or the application of these products. Users are recommended to consult the most recent edition of the technical data sheet. A copy of this will be provided upon request, or can be obtained from be.iko.com.