

Bitumen Paint

Description:

High performance protective liquid, based on bitumen and solvents.

Use:

Protection of substrates in iron, steel, concrete, brickwork and fiber cement against water.

Packaging:

5L metal tin (item number 02401710)

25L metal tin (item number 02401720)

Storage:

3 years in the hermetically sealed packaging, when stored in a dry and cool place.

Partly used containers may be resealed and used again after correct storage.

To avoid the risk of spillage, always store and transport in a secure upright position.

Colour:

Black

Technical characteristics:

Dry substance	+/- 50%
Density	+/- 0,88 g/cm ³
Viscosity	80-115mm ² /s (Ubelhode 40°C)

The technical information regarding the application of liquid waterproofing products supplied by IKO is provided in good faith on the basis of IKO's current know-how and experience, and assumes that these products will be used in accordance with the above-mentioned recommendations, under normal circumstances, and provided that these products were stored and handled in the correct manner. The above-mentioned information is only intended to inform the user about the various properties and/or recommendations and can in no way be considered as a guarantee with regard to the merchantability and suitability for a specific purpose in view of the continuously changing environmental factors, including the specific conditions at the building site, the use of different materials and substrates, etc. As a result, and with the exception of binding legal stipulations to the contrary, IKO cannot be held liable on the basis of the provided information, and any other written recommendations and/or advice. Please contact IKO if you have any doubts regarding the processing, the end use or the application of these products. Users are recommended to consult the most recent edition of the technical data sheet. A copy of this will be provided upon request, or can be obtained from be.iko.com.

Application:

The substrate needs to be sound, clean and free from grease and non-adhering particles.

Prime iron and steel surfaces with a suitable rust inhibiting primer, which must be thoroughly dry before further treatment.

Roughen galvanized surfaces with a wire brush or treat it with a suitable etching primer.

Consumption rate:

Metal surfaces: 2 layers of each 0,125 L/m²

Concrete and wood: 2 layers of each 0,25 L/m²

Cleaning of tools:

White Spirit

Certificates:

Production ISO 9001 & 14001

