

Repair Compound

Description:

Flexible bituminous sealing compound.

High and permanent adhesion to building materials such as bitumen roof felt, wood, metal, stone, plastic and concrete.

Use:

Filling, sealing and repairing joints, seams, tears and connections to flashing materials on bitumen roof felt, rooflights and aluminium roof trims.

Sealing when doing emergency repairs, even in humid conditions.

Packaging:

310mL plastic cartridges (item number 02401661)

5kg metal tin (item number 02401510)

Storage:

3 years in the hermetically sealed packaging, when stored in a dry and cool place.

Partly used containers may be resealed and used again after correct storage.

To avoid the risk of spillage, always store and transport in a secure upright position.

Colour:

Black

Technical characteristics:

Dry substance	+/- 86%
Density	+/- 1,3 g/cm ³
Viscosity	309.000-433.000 mPas (Haake 50°C)

Application:

The substrate needs to be sound, clean and free from grease and non-adhering particles.

Remove algae and fungi with IKO pro Algae and Fungi Remover.

Prime porous substrates and bitumen roof felts with IKO pro Bitumen Primer- Fast Dry Primer - ECO Primer.

Repair blisters and cracks using IKO pro Repair Compound applied with a trowel (product in tin) or with a gun (product in cartridge).

Consumption rate:

Depending on the depth and severity of the damage to be repaired.

± 3 linear m for a 1 cm x 1 cm joint

Cleaning of tools:

White Spirit

Certificates:

Production ISO 9001 & 14001



The technical information regarding the application of liquid waterproofing products supplied by IKO is provided in good faith on the basis of IKO's current know-how and experience, and assumes that these products will be used in accordance with the above-mentioned recommendations, under normal circumstances, and provided that these products were stored and handled in the correct manner. The above-mentioned information is only intended to inform the user about the various properties and/or recommendations and can in no way be considered as a guarantee with regard to the merchantability and suitability for a specific purpose in view of the continuously changing environmental factors, including the specific conditions at the building site, the use of different materials and substrates, etc. As a result, and with the exception of binding legal stipulations to the contrary, IKO cannot be held liable on the basis of the provided information, and any other written recommendations and/or advice. Please contact IKO if you have any doubts regarding the processing, the end use or the application of these products. Users are recommended to consult the most recent edition of the technical data sheet. A copy of this will be provided upon request, or can be obtained from be.iko.com.