

# Wall Paint

## Description:

Semi-glossy white and solventfree acrylic paint.

## Use:

Decorative and water-repellent protection of interior and exterior walls.

Suitable for brick, cement-work, masonry, fibro-cement, concrete, plaster..

## Packaging:

5L metal tin (item number 02400630)

## Storage:

3 years in the hermetically sealed packaging, when stored in a dry, cool and frostfree place.

Partly used containers may be resealed and used again after correct storage.

To avoid the risk of spillage, always store and transport in a secure upright position.

## Colour:

White

## Technical characteristics:

Dry substance	+/- 54%
Density	+/- 1,3 g/cm <sup>3</sup>
Viscosity	20% Torque (Brookfield 25°C, spindle 6/20rpm)

## Application:

The substrate needs to be sound, clean and free from grease and non-adhering particles.

Algae and fungi must be removed with a stiff broom and the surface treated with IKO pro Algae and Fungi Remover.

Porous substrates should be primed with a layer of IKO pro Acryl Primer.

Check the condition of the joints; crumbling grouting must first be repaired.

The application and curing temperature should be between 5°C and 35°C.

Stir well before use.

Apply IKO pro Wall Paint using a brush, a roller or an airless gun (opening 0.025 inches).

## Consumption rate:

± 0,2 L/m<sup>2</sup>, in one or two layers

## Cleaning of tools:

Immediately with water

## Certificates:

Production ISO 9001 & 14001



The technical information regarding the application of liquid waterproofing products supplied by IKO is provided in good faith on the basis of IKO's current know-how and experience, and assumes that these products will be used in accordance with the above-mentioned recommendations, under normal circumstances, and provided that these products were stored and handled in the correct manner. The above-mentioned information is only intended to inform the user about the various properties and/or recommendations and can in no way be considered as a guarantee with regard to the merchantability and suitability for a specific purpose in view of the continuously changing environmental factors, including the specific conditions at the building site, the use of different materials and substrates, etc. As a result, and with the exception of binding legal stipulations to the contrary, IKO cannot be held liable on the basis of the provided information, and any other written recommendations and/or advice. Please contact IKO if you have any doubts regarding the processing, the end use or the application of these products. Users are recommended to consult the most recent edition of the technical data sheet. A copy of this will be provided upon request, or can be obtained from [be.iko.com](https://be.iko.com).