

Tinascoat

Description:

Ready to use cold applied hydrocarbon.

IKO pro Tinascoat retains a high internal flexibility and never fully cures.

Use:

Temporary repair or resurfacing of hydrocarbon surfacing subjected to light or medium traffic, like surfaces of public highways, drives, garage entrances or forecourts, car parks and factory yards.

Packaging:

25kg plastic bag (item number 0007202)

25kg plastic tin (item number 0007201)

Storage:

6 months in the hermetically sealed packaging, when stored in a dry and cool place.

Colour:

Black

Application:

Cut out the degraded area to give it clean edges.

Clean the surface using a wire brush. Remove any water or mud.

Always daub the bottom and edges of the area under repair with IKO Bitumix CE, at a rate of 0,2-0,3 kg/m².

Spread IKO pro Tinascoat with a rake and compact it with a rammer or other suitable equipment.

The IKO pro Tinascoat layer must not exceed 3 cm after compacting. If the deterioration is deeper than this, provide an underlayer of well compacted small stones (size 0/22).

Sand IKO pro Tinascoat at high temperatures.

Consumption rate:

± 25 kg/m² and per centimetre of thickness

Cleaning of tools:

White Spirit

Certificates:

Production ISO 9001 & 14001



The technical information regarding the application of liquid waterproofing products supplied by IKO is provided in good faith on the basis of IKO's current know-how and experience, and assumes that these products will be used in accordance with the above-mentioned recommendations, under normal circumstances, and provided that these products were stored and handled in the correct manner. The above-mentioned information is only intended to inform the user about the various properties and/or recommendations and can in no way be considered as a guarantee with regard to the merchantability and suitability for a specific purpose in view of the continuously changing environmental factors, including the specific conditions at the building site, the use of different materials and substrates, etc. As a result, and with the exception of binding legal stipulations to the contrary, IKO cannot be held liable on the basis of the provided information, and any other written recommendations and/or advice. Please contact IKO if you have any doubts regarding the processing, the end use or the application of these products. Users are recommended to consult the most recent edition of the technical data sheet. A copy of this will be provided upon request, or can be obtained from be.iko.com.