

IKO carrara G 5

01567575

Description:

Waterproofing membrane composed of elastomer (SBS) bitumen with fire-retardant properties and a polyester-glass combination inlay. The upper surface is finished with white titanium dioxide slates (SRI 45) and the lower surface is protected by a thermofusible film. This top layer can be applied in a single- or multi-layer system. This top layer contains $\geq 30\%$ secondary raw materials by roll weight. This roofing membrane is 100 % recyclable.

Installation

Installation: fully torched-on.

Composition

| | |
|----------------------|--|
| Type of bitumen | Elastomeric |
| Upper surface finish | White slates |
| Inlay | Polyester-glass combination 270 g/m ² (trilaminate) |
| Lower surface finish | Thermofusible film |

Technical characteristics:

| | |
|--|-----------------------|
| Tensile strength L (EN 12311-1 MDV N/50 mm +/- 20%) | 1300 |
| Tensile strength T (EN 12311-1 MDV N/50 mm +/- 20%) | 1000 |
| Elongation L (EN 12311-1 MDV % +/- 15% abs.) | 45 |
| Elongation B (EN 12311-1 MDV % +/- 15% abs.) | 45 |
| Nail tear resistance(EN 12310-1 MDV N Only MF) | $\geq 200 / \geq 250$ |
| Flexibility at low temperature (EN 1109 MLV °C Surface/Bottom) | ≤ -25 |
| Flow temperature (EN 1110) | ≥ 110 |
| Shear resistance (EN 12317-1 MDV N/50 mm) | ≥ 500 |
| Dimensional stability (EN 1107-1 MLV) | ≤ 0.3 |
| Fire resistance | Broof(t1-t3) |
| Vapour diffusion resistance (μ d) | NPD |
| Root resistant (EN 13948) | - |

Sizing and palletization:

| | |
|--------------------------|-------------|
| Nominal thickness (mm) | 5,0 |
| Thickness tolerance (mm) | +/- 0,2 |
| Length (m) | 5 |
| Width (m) | 1 |
| Width of overlap (cm) | 8,0 |
| Weight per roll(kg) | +/- 30 |
| Number of rolls / pallet | 24 |
| Type of pallet | Euro-pallet |

Always use a suitable pallet hoisting hook for vertical transport.

Certificates:

- Production ISO 9001 & 14001

IKO hereby certifies that this construction product complies with the provisions of the following European Directive(s) if installed in accordance with the system directions and installation rules set out in the documentation:

- Council Directive 89/106/EEC on Construction Products
- EN 13707

FPC certificate obtained from SGS Notified Body, registered under registration number 0958.

Certificate number: 0958-CPR-2009/1.

