

IKO powergum 4 T/MMP 7.5 m

01512646

Description:

Waterproofing membrane composed of plastomer (APP) bitumen with fire-retardant properties and a polyester-glass combination inlay. The upper surface is finished with sand and the lower surface is protected by a macro-perforated thermofusible film. This top layer can be applied in a single- or multi-layer system. This roofing membrane is 100 % recyclable.

Installation

Installation: fully torched-on, bonded with bituminous cold glue or loosely laid and ballasted

Composition

| | |
|----------------------|--|
| Type of bitumen | Plastomeric |
| Upper surface finish | Sand |
| Inlay | Polyester-glass combination 180 g/m ² |
| Lower surface finish | Macro-perforated thermofusible film (MMP) |

Technical characteristics:

| | |
|--|-----------|
| Tensile strength L (EN 12311-1 MDV N/50 mm +/- 20%) | 700 |
| Tensile strength T (EN 12311-1 MDV N/50 mm +/- 20%) | 450 |
| Elongation L (EN 12311-1 MDV % +/- 15% abs.) | 20 |
| Elongation B (EN 12311-1 MDV % +/- 15% abs.) | 40 |
| Nail tear resistance(EN 12310-1 MDV N Only MF) | ≥ 150 |
| Flexibility at low temperature (EN 1109 MLV °C Surface/Bottom) | ≤ -15 |
| Flow temperature (EN 1110) | ≥ 130 |
| Shear resistance (EN 12317-1 MDV N/50 mm) | ≥ 500 |
| Dimensional stability (EN 1107-1 MLV) | ≤ 0.3 |
| Fire resistance | Broof(t1) |
| Vapour diffusion resistance (μd) | ≥ 200 m |
| Root resistant (EN 13948) | - |

Sizing and palletization:

| | |
|--------------------------|----------------------------|
| Nominal thickness (mm) | 4,0 |
| Thickness tolerance (mm) | +/- 0,2 |
| Length (m) | 7,5 |
| Width (m) | 1 |
| Width of overlap (cm) | 8,0 |
| Weight per roll(kg) | +/- 38 |
| Number of rolls / pallet | 25 |
| Type of pallet | 1 x 1,2 m guarantee pallet |

Always use a suitable pallet hoisting hook for vertical transport.

Certificates:

- ATG 1337
- CTG 498
- Production ISO 9001 & 14001

IKO hereby certifies that this construction product complies with the provisions of the following European Directive(s) if installed in accordance with the system directions and installation rules set out in the documentation:

- Council Directive 89/106/EEC on Construction Products
- EN 13707

FPC certificate obtained from SGS Notified Body, registered under registration number 0958.

Certificate number: 0958-CPR-2009/1.

