

## IKO powerflex 4 T/F ICE 8 m

**01550407**

### Description:

Waterproofing membrane composed of elastomer (SBS) bitumen with a polyester-glass combination inlay. The upper surface is finished with talc and the lower surface is protected by a thermofusible film. This top layer can be applied in a single- or multi-layer system.

### Installation

Installation: fully torched-on or loosely laid and ballasted

### Composition

|                      |  |
|----------------------|--|
| Type of bitumen      | Elastomeric                                      |
| Upper surface finish | Talc   |
| Inlay                | Polyester-glass combination 180 g/m <sup>2</sup> |
| Lower surface finish | Thermofusible film                               |

### Technical characteristics:

|  |        |
|--|--------|
| Tensile strength L (EN 12311-1 MDV N/50 mm +/- 20%)            | 800    |
| Tensile strength T (EN 12311-1 MDV N/50 mm +/- 20%)            | 600    |
| Elongation L (EN 12311-1 MDV % +/- 15% abs.)                   | 40     |
| Elongation B (EN 12311-1 MDV % +/- 15% abs.)                   | 50     |
| Nail tear resistance(EN 12310-1 MDV N Only MF)                 | ≥ 200  |
| Flexibility at low temperature (EN 1109 MLV °C Surface/Bottom) | ≤ -20  |
| Flow temperature (EN 1110)                                     | ≥ 110  |
| Shear resistance (EN 12317-1 MDV N/50 mm)                      | 500    |
| Dimensional stability (EN 1107-1 MLV)                          | ≤ 0.3  |
| Fire resistance  | Proof  |
| Vapour diffusion resistance (μd)                               | ≥ 80 m |
| Root resistant (EN 13948)                                      | -      |

### Packaging:

|                          |                      |
|--------------------------|----------------------|
| Nominal thickness (mm)   | +/- 4                |
| Thickness tolerance (mm) | -                    |
| Length (m)               | 8                    |
| Width (m)                | 1                    |
| Width of overlap (cm)    | 8,0                  |
| Weight per roll(kg)      | +/- 41,5             |
| Number of rolls / pallet | 20                   |
| Type of pallet           | 1 X 1,2 m single use |

### Certificates:

- Production ISO 9001 & 14001

IKO hereby certifies that this construction product complies with the provisions of the following European Directive(s) if installed in accordance with the system directions and installation rules set out in the documentation:

- Council Directive 89/106/EEC on Construction Products
- EN 13707
- EN 13969

FPC certificate obtained from SGS Notified Body, registered under registration number 0958.

Certificate number: 0958-CPR-2009/1.

