

IKO powerflex mono 3 MB 6 m

01564085

Description:

Waterproofing membrane composed of elastomer (SBS) bitumen with fire-retardant properties and a polyester-glass combination inlay. The upper surface is finished with dark grey crushed slate and the lower surface is protected by a PP fleece. This top layer can be applied in a single-layer system.

Installation

Installation: mechanically fastened, overlaps welded with hot air.

Composition

| | |
|----------------------|--|
| Type of bitumen | Elastomeric |
| Upper surface finish | Dark grey crushed slate |
| Inlay | Polyester-glass combination 180 g/m ² |
| Lower surface finish | PP fleece |

Technical characteristics:

| | |
|--|--------------|
| Tensile strength L (EN 12311-1 MDV N/50 mm +/- 20%) | 800 |
| Tensile strength T (EN 12311-1 MDV N/50 mm +/- 20%) | 600 |
| Elongation L (EN 12311-1 MDV % +/- 15% abs.) | 40 |
| Elongation B (EN 12311-1 MDV % +/- 15% abs.) | 50 |
| Nail tear resistance(EN 12310-1 MDV N Only MF) | ≥ 150 |
| Flexibility at low temperature (EN 1109 MLV °C Surface/Bottom) | ≤ -20 |
| Flow temperature (EN 1110) | ≥ 110 |
| Shear resistance (EN 12317-1 MDV N/50 mm) | ≥ 500 |
| Dimensional stability (EN 1107-1 MLV) | ≤ 0.3 |
| Fire resistance | Broof(t1-t4) |
| Vapour diffusion resistance (μd) | NPD |
| Root resistant (EN 13948) | - |

Sizing and palletization:

| | |
|--------------------------|----------------------|
| Nominal thickness (mm) | 3,2 |
| Thickness tolerance (mm) | +/- 0,2 |
| Length (m) | 6 |
| Width (m) | 1 |
| Width of overlap (cm) | 12,0 |
| Weight per roll(kg) | +/- 27 |
| Number of rolls / pallet | 30 |
| Type of pallet | 1 X 1,2 m single use |

Always use a suitable pallet hoisting hook for vertical transport.

Certificates:

- CTG 499
- IAB 08/0316
- FM Approval (External Fire Rating A)
- Production ISO 9001 & 14001

IKO hereby certifies that this construction product complies with the provisions of the following European Directive(s) if installed in accordance with the system directions and installation rules set out in the documentation:

- Council Directive 89/106/EEC on Construction Products
- EN 13707

FPC certificate obtained from SGS Notified Body, registered under registration number 0958.

Certificate number: 0958-CPR-2009/1.

