

IKO base Stick T/SA 15 m x 1.08 m

01570711

Description:

Underlayer composed of polymer bitumen and a polyester-glass combination inlay. This underlay is finished with sand on the upper surface and a self-adhesive lower surface.

Installation

Installation: fully self-adhesive with IKO pro SA primer (except on IKO enertherm ALU or MG against upstands and on painted steeldeck - use no primer)

Installation temperature (based on self-adhesive placement only) $\geq 5^{\circ}\text{C}$.

At temperatures $\leq 10^{\circ}\text{C}$. The rolls should be stored in a room $\geq 10^{\circ}\text{C}$ before installation.

Composition

| | |
|----------------------|--|
| Type of bitumen | Polymer |
| Upper surface finish | Sand |
| Inlay | Polyester-glass combination 150 g/m ² |
| Lower surface finish | Self-adhesive bitumen with anti-stick film |

Technical characteristics:

| | |
|--|----------------------|
| Tensile strength L (EN 12311-1 MDV N/50 mm +/- 20%) | 525 |
| Tensile strength T (EN 12311-1 MDV N/50 mm +/- 20%) | 350 |
| Elongation L (EN 12311-1 MDV % +/- 15% abs.) | 30 |
| Elongation B (EN 12311-1 MDV % +/- 15% abs.) | 40 |
| Nail tear resistance(EN 12310-1 MDV N Only MF) | ≥ 100 |
| Flexibility at low temperature (EN 1109 MLV °C Surface/Bottom) | $\leq -5/-25$ |
| Flow temperature (EN 1110) | ≥ 100 |
| Shear resistance (EN 12317-1 MDV N/50 mm) | NPD |
| Dimensional stability (EN 1107-1 MLV) | ≤ 0.5 |
| Fire resistance | Froof |
| Vapour diffusion resistance (μd) | $\geq 125 \text{ m}$ |
| Root resistant (EN 13948) | - |

Sizing and palletization:

| | |
|--------------------------|-------------|
| Nominal thickness (mm) | 2,5 |
| Thickness tolerance (mm) | +/- 0,2 |
| Length (m) | 15 |
| Width (m) | 1,08 |
| Width of overlap (cm) | 8,0 |
| Weight per roll(kg) | +/- 44,5 |
| Number of rolls / pallet | 15 |
| Type of pallet | Euro-pallet |

Always use a suitable pallet hoisting hook for vertical transport.

Certificates:

- Production ISO 9001 & 14001

IKO hereby certifies that this construction product complies with the provisions of the following European Directive(s) if installed in accordance with the system directions and installation rules set out in the documentation:

- Council Directive 89/106/EEC on Construction Products
- EN 13707
- En 13969

FPC certificate obtained from SGS Notified Body, registered under registration number 0958.

Certificate number: 0958-CPR-2009/1.

