Aluminium Paint

Description:

Solar reflective bitumen paint, enriched with aluminium pigments.

Use:

Solar reflective protection of bitumen roof felt against UV rays and weathering. Do not apply on APP modified bitumen roof felt without slate finishing.

Sizing and palletization:

5L metal tin (item number 02401760)

25L metal tin (item number 02401770)

Storage:

2 years in the hermetically sealed packaging, when stored in a dry and cool place.

Partly used containers may be resealed and used again after correct storage.

To avoid the risk of spillage, always store and transport in a secure upright position.

Colour:

Metal



Application:

The substrate needs to be sound, clean and free from grease and non-adhering particles.

Prime porous substrates and bitumen roof felts with IKO pro Bitumen Primer- Fast Dry Primer - ECO Primer.

Stir IKO pro Aluminium paint thoroughly before use and during application.

Apply IKO pro Aluminium Paint over the roof surface with a soft broom or roller.

For maximum durability and reflectivity, apply 2 layers. Allow the first layer to dry thoroughly before the application of the second layer, normally after 24 hours, depending on the temperature and the weather conditions.

In order to avoid craquelé formation, the coating can't be subjected to ponding water while curing.

Consumption rate:

0,125-0,167 L/m² per layer - respect the consumption rate

Cleaning of tools:

White Spirit

The technical information regarding the application of liquid waterproofing products supplied by IKO is provided in good faith on the basis of IKO's current know-how and experience, and assumes that these products will be used in accordance with the above-mentioned recom-mendations, under normal circumstances, and provided that these products were stored and handled in the correct manner. The above-mentioned information is only intended to inform the user about the various properties and/or recommendations and can in no way be consid-ered as a guarantee with regard to the merchantability and suitability for a specific purpose in view of the continuously changing environmental factors, including the specific conditions at the building site, the use of different materials and substrates, etc. As a result, and with the exception of binding legal stipulations to the contrary, IKO cannot be held liable on the basis of the provided information, and any other written recommendations and/or advice. Please contact IKO if you have any doubts regarding the processing, the end use or the application of these products. Users are recommended to consult the most recent edition of the technical data sheet. A copy of this will be provided upon request, or can be obtained from https://eu.iko.com.