

# Ascopact

## Description:

---

Additive for mortar based on an emulsion, in order to improve the adhesion between the mortar and the support.

## Use:

---

Realisation of very thin screeds, levelling of floors, dust-free mortar layers, etc.

Restoration and tidying up of concrete constructions, cracks, gravel pockets.

Cementing of cellars.

## Packaging:

---

Jerrican of 5L (item number 024002100)

Jerrican of 25L (item number 024002105)

## Storage:

---

3 years in the hermetically sealed packaging, when stored in a dry, cool and frostfree place.

Partly used containers may be resealed and used again after correct storage.

To avoid the risk of spillage, always store and transport in a secure upright position.

## Colour:

---

Milky white

## Application:

---

First mix IKO pro Ascopact with the mortar, then add water.

IKO pro Ascopact can be applied directly to porous and non-porous surfaces to obtain a better adhesion.

## Consumption rate:

---

1L per 50 kg cement, or 5L per 50 kg cement for completely watertight mortar

## Cleaning of tools:

---

Immediately with water

## Certificates:

---

Production ISO 9001 & 14001



For further information, please consult the Declaration Of Performance 02400817 010713.

---

The technical information regarding the application of liquid waterproofing products supplied by IKO is provided in good faith on the basis of IKO's current know-how and experience, and assumes that these products will be used in accordance with the above-mentioned recommendations, under normal circumstances, and provided that these products were stored and handled in the correct manner. The above-mentioned information is only intended to inform the user about the various properties and/or recommendations and can in no way be considered as a guarantee with regard to the merchantability and suitability for a specific purpose in view of the continuously changing environmental factors, including the specific conditions at the building site, the use of different materials and substrates, etc. As a result, and with the exception of binding legal stipulations to the contrary, IKO cannot be held liable on the basis of the provided information, and any other written recommendations and/or advice. Please contact IKO if you have any doubts regarding the processing, the end use or the application of these products. Users are recommended to consult the most recent edition of the technical data sheet. A copy of this will be provided upon request, or can be obtained from [be.iko.com](https://be.iko.com).