

ECO Primer

Description:

Solventfree bitumen primer (waterbased emulsion) designed to activate and prepare substrates prior to the application of bitumen waterproofing products.

Drying time approximately 2 hours at 20°C , depending on the substrate and the weather conditions.

Use:

Activation of the substrate prior to the application of IKO roofing bitumen roof felts and IKO pro liquid products.

May be applied to many substrates including concrete, brickwork, metal and existing bitumen roof felt.

Sizing and palletization:

5L metal tin (item number 02401956)

25L metal tin (item number 02401957)

Storage:

12 months in the hermetically sealed packaging, when stored in a dry, cool and frostfree place.

Partly used containers may be resealed and used again after correct storage.

To avoid the risk of spillage, always store and transport in a secure upright position.

Colour:

Black

Technical characteristics:

Dry substance +/-42,5% Density +/- 0,98 g/cm³

Viscosity 3.500-4.500 mPas (Brookfield, 25°C, spindle 3, speed



Application:

The substrate needs to be sound, clean and free from grease and nonadhering particles.

Algae and fungi must be removed with a stiff broom and the surface treated with IKO pro Algae and Fungi Remover.

Apply IKO pro ECO Primer in one layer with a brush or roller.

Make sure the primer is dry before applying IKO roofing bitumen roof felts or liquid IKO pro products.

Consumption rate:

Bitumen: $\pm 0.2 \text{ L/m}^2$

Concrete: 0,25-0,3 L/m²

Metal: 0,07-0,1 L/m²

Fibre cement: 0,08-0,1 L/m²

Cleaning of tools:

With water while the product is still wet or with white spirit if dry.

Certificates:

Production ISO 9001 & 14001



The technical information regarding the application of liquid waterproofing products supplied by IKO is provided in good faith on the basis of IKO's current know-how and experience, and assumes that these products will be used in accordance with the above-mentioned recom-mendations, under normal circumstances, and provided that these products were stored and handled in the correct manner. The above-mentioned information is only intended to inform the user about the various properties and/or recommendations and can in no way be consid-ered as a guarantee with regard to the merchantability and suitability for a specific purpose in view of the continuously changing environmental factors, including the specific conditions at the building site, the use of different materials and substrates, etc. As a result, and with the exception of binding legal stipulations to the contrary, IKO cannot be held liable on the basis of the provided information, and any other written recommendations and/or advice. Please contact IKO if you have any doubts regarding the processing, the end use or the application of these products. Users are recommended to consult the most recent edition of the technical data sheet. A copy of this will be provided upon request, or can be obtained from https://eu.iko.com.