# Chipping Compound

## Description:

Liquid bitumen adhesive containing solvents.

## Use:

Broadcasting layer for chippings and aggregates on weathered bitumen roof felts.

## Sizing and palletization:

25L metal tin (item number 02401910)

## Storage:

3 years in the hermetically sealed packaging, when stored in a dry and cool place.

Partly used containers may be resealed and used again after correct storage.

To avoid the risk of spillage, always store and transport in a secure upright position.

## Colour:

Black

## Technical characteristics:

| | |
|---|---|
| Dry substance | +/- 75% |
| Density | +/- 0,94 g/cm³ |
| Viscosity | 3.500-4.500 mm²/s (Ubelhode 25°C) |




## Application:

The substrate needs to be sound, clean and free from grease and non-adhering particles.

Algae and fungi must be removed with a stiff broom and the surface treated with IKO pro Algae and Fungi Remover.

Prime porous substrates and bitumen roof felts with IKO pro Bitumen Primer- Fast Dry Primer - ECO Primer.

Apply IKO pro Chipping Compound by brush or squeegee and broadcast immediately with chippings or aggregates.

Once dry, brush off and remove the surplus of chippings.

## Consumption rate:

± 0,67 L/m²

## Cleaning of tools:

White Spirit

## Certificates:

Production ISO 9001 & 14001

The technical information regarding the application of liquid waterproofing products supplied by IKO is provided in good faith on the basis of IKO's current know-how and experience, and assumes that these products will be used in accordance with the above-mentioned recom-mendations, under normal circumstances, and provided that these products were stored and handled in the correct manner. The above-mentioned information is only intended to inform the user about the various properties and/or recommendations and can in no way be consid-ered as a guarantee with regard to the merchantability and suitability for a specific purpose in view of the continuously changing environmental factors, including the specific conditions at the building site, the use of different materials and substrates, etc. As a result, and with the exception of binding legal stipulations to the contrary, IKO cannot be held liable on the basis of the provided information, and any other written recommendations and/or advice. Please contact IKO if you have any doubts regarding the processing, the end use or the application of these products. Users are recommended to consult the most recent edition of the technical data sheet. A copy of this will be provided upon request, or can be obtained from https://eu.iko.com.