

Slate Paint

Description:

Mat black and solventfree acrylic paint.

Use:

Renovation and waterproof protection of roofs: artificial slates, tiles, fibre-cement (corrugated sheets...) and bitumen roof felt.

Sizing and palletization:

5L metal tin (item number 02400540)

20L metal tin (item number 02400545)

Storage:

3 years in the hermetically sealed packaging, when stored in a dry, cool and frostfree place.

Partly used containers may be resealed and used again after correct storage.

To avoid the risk of spillage, always store and transport in a secure upright position.

Colour:

Black

Technical characteristics:

Dry substance +/- 52% Density +/- 1,25 g/cm³

Viscosity 15-20% Torque (Brookfield 25°C, spindle 6/20rpm)



Application:

The substrate needs to be sound, clean and free from grease and nonadhering particles.

Algae and fungi must be removed with a stiff broom and the surface treated with IKO pro Algae and Fungi Remover.

Let the surface dry at least for 4 days in case of cleaning with water under pressure.

On porous surfaces like fibre-cement and artificial slates always apply a layer of IKO pro Acryl Primer.

The appication temperature should be between 5°C and 35°C.

Stir well before use.

Apply the paint with a brush, roller or airless nozzle spray.

Consumption rate:

± 0,2 L/m², in one or two layers

Cleaning of tools:

Immediately with water

Certificates:

Production ISO 9001 & 14001



The technical information regarding the application of liquid waterproofing products supplied by IKO is provided in good faith on the basis of IKO's current know-how and experience, and assumes that these products will be used in accordance with the above-mentioned recom-mendations, under normal circumstances, and provided that these products were stored and handled in the correct manner. The above-mentioned information is only intended to inform the user about the various properties and/or recommendations and can in no way be consid-ered as a guarantee with regard to the merchantability and suitability for a specific purpose in view of the continuously changing environmental factors, including the specific conditions at the building site, the use of different materials and substrates, etc. As a result, and with the exception of binding legal stipulations to the contrary, IKO cannot be held liable on the basis of the provided information, and any other written recommendations and/or advice. Please contact IKO if you have any doubts regarding the processing, the end use or the application of these products. Users are recommended to consult the most recent edition of the technical data sheet. A copy of this will be provided upon request, or can be obtained from https://eu.iko.com.