

# Zinc Renovation

## Description:

Liquid 2-component, waterproofing, self-nivelating and zinc coloured coating based on polyurethane, that forms a smooth and seamless reflecting surface after curing.

## Use:

Repairing and protecting in a sustainable way old and new metal roofs and gutters (zinc, copper, lead, aluminium, iron,...) against corrosion, acid rains, UV rays and other aggressive environmental influences.

Preventively protecting new metal substrates; extending the life expectancy of zinc, lead, aluminium, copper, iron,... considerably.

## Packaging:

1,5L metal tin (item number 02783401)

## Storage:

2 years in the hermetically sealed packaging, when stored in a dry, cool and frostfree place.

## Colour:

Metal

## Application:

The substrate needs to be sound, clean and free from grease, rust and non-adhering particles.

Roughen the substrate with a steel brush and degrease it using a solution of water and ammonia or a synthetic degreaser. Only treat new metals after 6 months.

Tape visible perforations in order to avoid spillage of the coating. Reinforce cracks by using the polyester fleece IKO protect Teknofleece, placed in the first layer of IKO pro Zinc Renovation.

Stir component A and B separately. Then add component A to component B. Mix intensively until a homogeneous zinc colour appears.

Pour the mix on the prepared substrate and divide this immediately using a brush or roller.

After mixing the 2 components the working time is  $\pm 30$  minutes at 20°C and  $\pm 60$  minutes at 10°C (temperature of the coating).

Once applied, protect against rain for  $\pm 4$  hours.

One layer should suffice. Under extreme circumstances, apply a second layer after 24 hours, once the first layer has been roughened with a steel brush.

## Consumption rate:

Per kit: 2,5 m<sup>2</sup> or  $\pm 8$  lm gutter with a width of 20 cm

## Cleaning of tools:

Mechanically once fully cured

## Certificates:

Production ISO 9001 & 14001



The technical information regarding the application of liquid waterproofing products supplied by IKO is provided in good faith on the basis of IKO's current know-how and experience, and assumes that these products will be used in accordance with the above-mentioned recommendations, under normal circumstances, and provided that these products were stored and handled in the correct manner. The above-mentioned information is only intended to inform the user about the various properties and/or recommendations and can in no way be considered as a guarantee with regard to the merchantability and suitability for a specific purpose in view of the continuously changing environmental factors, including the specific conditions at the building site, the use of different materials and substrates, etc. As a result, and with the exception of binding legal stipulations to the contrary, IKO cannot be held liable on the basis of the provided information, and any other written recommendations and/or advice. Please contact IKO if you have any doubts regarding the processing, the end use or the application of these products. Users are recommended to consult the most recent edition of the technical data sheet. A copy of this will be provided upon request, or can be obtained from [be.iko.com](https://be.iko.com).