IKO CP Primer

Description:

- Resin based adherence primer.
- Cold applied.
- Excellent adherence to concrete and asphalt before the application of bituminous products
- Binds loose particles to the surface.
- Can be applied on wet surfaces thanks to it water repulsive action.
- Ready to use.

Use:

IKO CP Primer has been developed as premium primer in order to create an excellent adherence of numerous bituminous products on concrete or asphalt surfaces.

Even with regular presence of water and dissolved salts, the adherence is excellent for a long period.

Characteristics:

- Easy to apply with brush or airless pistol
- Excellent adherence, even on wet surfaces.

Caracteristics:

- Viscosity at 25°C mm²/s: 60-90

Consumption rate:

0,1-0,2 L/m²

Implementation:

Preparation of the substrate

- The surface must be free of humidity, oils and fats and dust.
- IKO CP Primer can be applied with a brush or airless pistol. Take care not to breathe in fumes or gasses.
- Make sure the primer doesn't thicken, due to long exposure of open tin by hot weather. If applied, the layer might be too thick, negatively impacting the adherence

Application of IKO CP Primer

- The recommended drying time is minimum 15 minutes, on wet surfaces minimum 90 minutes.
- After applying IKO CP Primer, apply the bituminous coating or expansion joint mass in teh next few hours, definately the same day.
- In some cases, it can be useful to do an adherence test.

Storage:

Unopened, can be kept for at least 3 years by normal conditions

Sizing and palletization:

Metal 25L can (item number 02100130)

The technical information regarding the application of liquid waterproofing products supplied by IKO is provided in good faith on the basis of IKO's current know-how and experience, and assumes that these products will be used in accordance with the above-mentioned recommendations, under normal circumstances, and that these products were stored and handled in the correct manner. The above-mentioned information is only intended to inform the user about the various properties and/or recommendations. and can in no way be considered as a guarantee with regard to the merchantability and suitability for a specific purpose in view of the continuously changing environmental factors, including the specific conditions at the building site, the use of different materials and substrates, etc. As a result, and with the exception of binding legal stipulations to the contrary, IKO cannot be held liable on the basis of the provided information, and any other written recommendations and/or advice. Please contact IKO if you have any doubts regarding the processing, the end use or the application of these products. Users are recommended to consult the most recent edition of the technical data sheet. A copy of this will be provided upon request, or can be obtained from https://eu.iko.com.