

Activator Spray

Description:

Ready-to-use adhesive, that is used as a primer in order to improve the adhesion of self-adhesive roof membranes at roof upstands.

IKO pro Activator Spray can also be used as a contact adhesive for bitumen roof felt with a lower surface protected by a macro-perforated thermofusible film at roof upstands.

Use:

Improves the adhesion to the substrate of both self-adhesive roof membranes and of bitumen roof felt with a lower surface protected by a macro-perforated thermofusible film at roof upstands.

IKO pro Activator Spray is used as primer for the application of IKO carrara Secura on IKO enertherm MG insulation at roof upstands.

Packaging:

750 mL spray (item number 02402230)

Storage:

12 months in the hermetically sealed packaging, when stored in a dry and cool place.

To avoid the risk of spillage, always store and transport in a secure upright position.

Colour:

Black

Technical characteristics:

Dry substance	+/- 36,5%
Density	+/- 0,84 g/cm ³
Viscosity	600 -1.200cps (18 - 22°C)

Application:

The air temperature and the product temperature should be between 5°C and 30°C.

If necessary, the spray can be brought to the correct temperature by placing it in a bucket of cold or lukewarm water.

The surface should be dry, stable, clean and free of any loose particle.

Apply 1 or 2 coats, ensuring an even distribution of the primer is achieved.

If IKOpro Activator Spray is used a contact adhesive, both the substrate and the lower surface of the bitumen roof felt should be treated.

Allow the solvents to evaporate from the IKOpro Activator Spray layer for 5 to 10 minutes (at 10°C).

Apply the membrane to the prepared substrate and press down firmly.

Consumption rate:

3 - 5 m²/ spray

Cleaning of tools:

IKO pro gun Cleaner

Certificates:

Production ISO 9001 & 14001



current know-how and experience, and assumes that these products will be used in accordance with the above-mentioned recommendations, under normal circumstances, and provided that these products were stored and handled in the correct manner. The above-mentioned information is only intended to inform the user about the various properties and/or recommendations and can in no way be considered as a guarantee with regard to the merchantability and suitability for a specific purpose in view of the continuously changing environmental factors, including the specific conditions at the building site, the use of different materials and substrates, etc. As a result, and with the exception of binding legal stipulations to the contrary, IKO cannot be held liable on the basis of the provided information, and any other written recommendations and/or advice. Please contact IKO if you have any doubts regarding the processing, the end use or the application of these products. Users are recommended to consult the most recent edition of the technical data sheet. A copy of this will be provided upon request, or can be obtained from be.iko.com.