

IKO perkadox

Characteristics:

- Phthalate-free peroxide powder
- Containing 50% active ingredient
- ISO9001 & 14001

Use:

IKO perkadox is used as hardener/ catalyst for the different 2-component PMMA IKO metatech products and IKO route products.

Sizing and palletization:

100g plastic bag (item number 00095110)

25kg cardboard box (item number 00095112)

Application:

We refer to our technical installation guidelines.

Storage:

12 months in the hermetically sealed packaging, when stored in a dry, cool and frost-free place.

Safety information:

We refer to our safety data sheet (MSDS), more specifically sections 2, 4, 5, 6, 7 and 8.



Technical characteristics:

Dry substance	+/- 97,5
Density	+/- 0,64 g/cm ³

The technical information regarding the application of liquid waterproofing products supplied by IKO is provided in good faith on the basis of IKO's current know-how and experience, and assumes that these products will be used in accordance with the above-mentioned recommendations, under normal circumstances, and that these products were stored and handled in the correct manner. The above-mentioned information is only intended to inform the user about the various properties and/or recommendations. and can in no way be considered as a guarantee with regard to the merchantability and suitability for a specific purpose in view of the continuously changing environmental factors, including the specific conditions at the building site, the use of different materials and substrates, etc. As a result, and with the exception of binding legal stipulations to the contrary, IKO cannot be held liable on the basis of the provided information, and any other written recommendations and/or advice. Please contact IKO if you have any doubts regarding the processing, the end use or the application of these products. Users are recommended to consult the most recent edition of the technical data sheet. A copy of this will be provided upon request, or can be obtained from <https://eu.iko.com>.