

IKO quartzsand 0,6-1,2

Description:

IKO quartzsand 0,6-1,2 is a mixture of coloured quartz sand granules with excellent wearing resistance and resistance to indentation.

Use:

The IKO quartzsand 0,6-1,2 granules are used to prepare the IKO quartzsand mortar, that is applied as a stone carpet over the cured IKO tanetech Balcony waterproofing membrane.

Colour:

Standard mixture mixed grey, grafito, grafito eine, natural quartz, terracotta, redbrick, yellow beach and green wimbledon

Sizing and palletization:

25kg plastic bag

Mixed grey: 25kg plastic bag (item number 00095100)

Grafito: 25kg plastic bag (item number 00095128)

Grafitp Eine: 25kg plastic bag (item number 00095027)

Natural quartz: 25kg plastic bag (item number 00095018)

Terracotta: 25kg plastic bag (item number 00095101)

Redbrick: 25kg plastic bag (item number 00095022)

Yello Beach: 25kg plastic bag (item number 00095021)

Green Wimbledon: 25kg plastic bag (item number 00095020)



Technical characteristics:

Density: grain +/- 2,65 g/cm³

Storage:

Unlimited in the hermetically sealed packaging, when stored in a dry, cool and frost-free place.

Certificates:



The technical information regarding the application of liquid waterproofing products supplied by IKO is provided in good faith on the basis of IKO's current know-how and experience, and assumes that these products will be used in accordance with the above-mentioned recommendations, under normal circumstances, and that these products were stored and handled in the correct manner. The above-mentioned information is only intended to inform the user about the various properties and/or recommendations. and can in no way be considered as a guarantee with regard to the merchantability and suitability for a specific purpose in view of the continuously changing environmental factors, including the specific conditions at the building site, the use of different materials and substrates, etc. As a result, and with the exception of binding legal stipulations to the contrary, IKO cannot be held liable on the basis of the provided information, and any other written recommendations and/or advice. Please contact IKO if you have any doubts regarding the processing, the end use or the application of these products. Users are recommended to consult the most recent edition of the technical data sheet. A copy of this will be provided upon request, or can be obtained from www.ikoflexia.com.