

IKO tech Non Porous Primer

Characteristics:

- General purpose primer with excellent penetration properties
- Single-component and solvent based
- Fast drying
- Production ISO9001 & 14001

Use:

IKO tech Non Porous Primer is used as primer for the liquid waterproofing systems IKO tanetech R-EC/UV, IKO tanetech Detail and IKO tanetech Balcony on

- Bitumen membranes
- A selection of single ply membranes (please contact IKO)
- Metals
- Hard plastics
- Treated wood

IKO tech Non porous Primer is also used as primer for the liquid waterproofing systems IKO metatech Roof, IKO metatech Detail, IKO metatech Balcony and IKO metatech Car Park on

- Metals
- Resitrix

IKO tech Non Porous Primer is also used as primer for the liquid waterproofing systems IKO hybritech MS Detail, IKO hybritech Roof en IKO hybritech Detail on

- Hard PE
- A selection of single ply membranes (please contact IKO)

Sizing and palletization:

IKO tech Non Porous Primer:

- Transparent: 1L metal tin (item number 02401810) and 5L metal tin (item number 00013029)

Application:

We refer to our technical installation guidelines

Air temperature	5°C - 35°C
Substrate temperature	5°C - 30°C
Product temperature	5°C - 30°C

The temperature of the substrate should remain min. 3°C higher than the dew point during application and curing.

Substrate preparation:

We refer to our technical installation guidelines.

Cleaning of tools:

IKO tech Cleaner

Storage:

36 months in the hermetically sealed packaging, when stored in a dry, cool and frost-free place.

Keep the edges of the tin clean.

When closing the tin, place the lid in the correct way and remove any product that might remain on the tin.



Technical characteristics:

Dry substance	+/- 31%
Density	+/- 1 g/cm ³
Viscosity	fordcup 4mm: 16s (25°C)

Consumption rate:

0,1 - 0,2 L/m²



Safety information:

We refer to our safety data sheet (MSDS), more specifically sections 2, 4, 5, 6, 7 and 8.

The technical information regarding the application of liquid waterproofing products supplied by IKO is provided in good faith on the basis of IKO's current know-how and experience, and assumes that these products will be used in accordance with the above-mentioned recommendations, under normal circumstances, and that these products were stored and handled in the correct manner. The above-mentioned information is only intended to inform the user about the various properties and/or recommendations, and can in no way be considered as a guarantee with regard to the merchantability and suitability for a specific purpose in view of the continuously changing environmental factors, including the specific conditions at the building site, the use of different materials and substrates, etc. As a result, and with the exception of binding legal stipulations to the contrary, IKO cannot be held liable on the basis of the provided information, and any other written recommendations and/or advice. Please contact IKO if you have any doubts regarding the processing, the end use or the application of these products. Users are recommended to consult the most recent edition of the technical data sheet. A copy of this will be provided upon request, or can be obtained from <https://eu.iko.com>.