

IKO ROUTE ADHESIVE

Description:

Cold applied 2 component glue based on PMMA.

Use:

IKO route Adhesive is used to glue different elements on a surface.

Characteristics:

- Elastic
- UV resistant
- Excellent adhesion
- Cold applied
- Quick hardening
- High resistance to fuels
- Color: black

Cleaning tools and stains:

With ethyl acetate, Acetone ...

Implementation:

On asphalt:

- On a clean and dry surface, free from flux oils (asphalt must be old enough, at least 8 weeks) In all the other cases, us IKO protect Metatec Finish.

On concrete:

- On a clean and dry surface applying IKO protect metaprim as primer before using IKO route Adhesive.
- It's preferred to prepare the fixed elements before with IKO protect Metaprim and to stick some dry sand it to the primer to have a better adhesion.
- Mix the IKO route Adhesive with a mechanical mixer for 30 seconds. Afterwards put in the exact quantity of Perkadox (bag of 100 gr) and mix again for 1 minute. Product is ready to us.

Storage:

POT-LIFE:

- +/- 10 minutes at 20°C

CURING TIME:

- +/- 30 minutes at 20 °C

12 months in hermetically sealed pails.

Packaging:

- IKO route Adhesive pails of 5 kg
- Perkadox bag of 100 gr (to be ordered separately)