

Hydrofuge X

Description:

Colourless and water-repellent impregnation for exterior walls.

Water vapor permeable hydrophobic agent based on moisture-proof silane-siloxane resins.

Concentration active ingredient of 10% for long lasting effect.

Use:

Waterproof protection of porous materials such as brick, mortar, masonry, concrete, fiber-cement and the like.

Preventative treatment of constructions that continually suffer from exposure to rain.

Not suitable for the treatment of less porous materials, like natural stone.

Sizing and palletization:

5L metal tin (item number 02400665)

25L metal tin (item number 02400672)

Storage:

36 months in the hermetically sealed packaging, when stored in a dry, cool and frostfree place.

Partly used containers may be resealed and used again after correct storage.

To avoid the risk of spillage, always store and transport in a secure upright position.

Colour:

Transparent

Technical characteristics:

Dry substance	10%
Density	0,8 kg/L



Application:

The substrate needs to be dry, at least 3 consecutive days without rain.

The substrate needs to be sound, clean and free from grease and non-adhering particles.

Remove the existing efflorescence first by washing the surface with diluted acid (1 litre chloric acid or hydrogen chloride per 40 litres of water) followed by thorough cleaning with water.

Algae and fungi must be removed with a stiff broom and the surface treated with IKO pro Algae and Fungi Remover.

Check the condition of the joints; repair weathered joints and cracks > 0,2mm beforehand.

Only apply IKO pro Hydrofuge X to masonry that is at least one month old, with joints that have completely cured.

The application temperature should be between 5°C and 25°C. Don't apply in the full sun.

Treat the substrate until complete saturation, until the product no longer penetrates the material: crosswise, with a low pressure spray unit, in one or two layers or with a brush or roller, in 2 layers, with approximately 2 hours between both layers.

Consumption rate:

0.25 to 1.20 L/m², depending on the absorption by the substrate

Cleaning of tools:

Immediately with White-Spirit

Certificates:

Production ISO 9001 & 14001



The technical information regarding the application of liquid waterproofing products supplied by IKO is provided in good faith on the basis of IKO's current know-how and experience, and assumes that these products will be used in accordance with the above-mentioned recommendations, under normal circumstances, and provided that these products were stored and handled in the correct manner. The above-mentioned information is only



intended to inform the user about the various properties and/or recommendations and can in no way be considered as a guarantee with regard to the merchantability and suitability for a specific purpose in view of the continuously changing environmental factors, including the specific conditions at the building site, the use of different materials and substrates, etc. As a result, and with the exception of binding legal stipulations to the contrary, IKO cannot be held liable on the basis of the provided information, and any other written recommendations and/or advice. Please contact IKO if you have any doubts regarding the processing, the end use or the application of these products. Users are recommended to consult the most recent edition of the technical data sheet. A copy of this will be provided upon request, or can be obtained from be.iko.com.