

# Wall Inject Gel

## Description:

Damp proof injection for treating rising damp in walls.  
Cream based on moisture-proof silane-siloxane resins.  
The treated pores remain open: the treated wall can fully dry up.  
Concentration active ingredient of 80% for long lasting effect.

## Use:

Treatment of interior and exterior walls against rising damp.  
Forms a horizontal moisture barrier in the wall.  
Effective after 48h.

## Packaging:

600mL Sausage (item number 02400650)

## Storage:

12 months in the hermetically sealed packaging, when stored in a dry, cool and frostfree place.

## Colour:

White

## Technical characteristics:

Active substance	+/- 80%
Density	+/- 0,9 g/cm <sup>3</sup>

## Application:

The application temperature should be between 5°C and 30°C.  
For the best result, remove skirting boards, plasterwork, wallpaper, paint, etc. up to one metre above the injection holes.  
Thoroughly inspect the joint pattern and repair where necessary to avoid leakage.  
Horizontally drill 10mm diameter holes into a horizontal joint at a height of 5 to 7cm from the floor, at distances of 12cm from one another and to a depth of up to 4/5 of the thickness of the wall. For walls thicker than 40cm, repeat the procedure on the other side of the wall.

Use a sausage kit gun to completely fill the drill holes with IKOpro Wall Inject Gel.

## Consumption rate:

Strongly dependent on the porosity, type, age and the pore size distribution of the treated wall.  
On average: 110mL per metre length of wall and per 10cm of wall thickness.

## Cleaning of tools:

Immediately with water

## Certificates:

CSTC report REN-20-047-01: classification A+  
Production ISO 9001 & 14001



The technical information regarding the application of liquid waterproofing products supplied by IKO is provided in good faith on the basis of IKO's current know-how and experience, and assumes that these products will be used in accordance with the above-mentioned recommendations, under normal circumstances, and provided that these products were stored and handled in the correct manner. The above-mentioned information is only intended to inform the user about the various properties and/or recommendations and can in no way be considered as a guarantee with regard to the merchantability and suitability for a specific purpose in view of the continuously changing environmental factors, including the specific conditions at the building site, the use of different materials and substrates, etc. As a result, and with the exception of binding legal stipulations to the contrary, IKO cannot be held liable on the basis of the provided information, and any other written recommendations and/or advice. Please contact IKO if you have any doubts regarding the processing, the end use or the application of these products. Users are recommended to consult the most recent edition of the technical data sheet. A copy of this will be provided upon request, or can be obtained from [be.iko.com](https://be.iko.com).