IKO drip Strip

Characteristics:

- Industrially produced pre-fabricated spitter from polymer resin for vertical components and façades.
- ISO9001 & 14001
- Fire class B1

Use:

The spitters avoid and prevent dirt, patina and dust deposits on façades

Sizing and palletization:

Dimensions 1.000mm length - 15mm width - 40mm height (item number 00095115)

Dimensions 1.000mm length - 30mm width - 50mm height (item number 00095117)

Application:

The water spitter must be glued by using an appropriate adhesive or mastic compound.

The water spitter must be covered with the IKO liquid waterproofing.

Storage:

Unlimited



Technical characteristics:

Density	+/- 600 kg/m³
Void content	+/- 25%

The technical information regarding the application of liquid waterproofing products supplied by IKO is provided in good faith on the basis of IKO's current know-how and experience, and assumes that these products will be used in accordance with the above-mentioned recommendations, under normal circumstances, and that these products were stored and handled in the correct manner. The above-mentioned information is only intended to inform the user about the various properties and/or recommendations. and can in no way be considered as a guarantee with regard to the merchantability and suitability for a specific purpose in view of the continuously changing environmental factors, including the specific conditions at the building site, the use of different materials and substrates, etc. As a result, and with the exception of binding legal stipulations to the contrary, IKO cannot be held liable on the basis of the provided information, and any other written recommendations and/or advice. Please contact IKO if you have any doubts regarding the processing, the end use or the application of these products. Users are recommended to consult the most recent edition of the technical data sheet. A copy of this will be provided upon request, or can be obtained from https://eu.iko.com.