

# Gutter Renovation

## Description:

Solventfree, odourfree, ready to use and self levelling coating based on flexible hybrid polymers.

## Use:

- Repairing leaking roof gutters made of all commonly used materials in a sustainable way.
- Protecting roof gutters against corrosion, acidic rain, UV rays and other environmental influences.

## Sizing and palletization:

Metal tin of 2,5L (item number 02400902)

## Storage:

12 months in the hermetically sealed packaging, when stored in a dry, cool and frost-free place.

Keep the edges of the tin clean.

When closing the tin, place the lid and the lever lock ring in the correct way and remove any product that might remain on the tin.

Once opened, use the product within 1 month. A skin will form on top of the product that needs to be cut out and can't be mixed to the liquid product.

## Colour:

Grey

## Technical characteristics:

Dry substance	> 96%
Density	+/- 1,48 g/cm <sup>3</sup>
Viscosity	+/- 20.000 cPs (25°C, spindle 7, spindle 10)
Hardness	+/- 70 (Shore A 23°C)
Tensile strength	+/- 3 N/mm <sup>2</sup>
Elongation	+/- 130%



## Application:

- The surface must be clean, dry and free from rust, grease and loose particles.
- First roughen the surface to be treated by using a metallic brush. Degrease the surface with a solution of ammonia and water or with a synthetic degreaser.
- Tape visible perforations in order to avoid the liquid coating flowing.
- Pour IKOpro Gutter Renovation on the prepared substrate and immediately divide this using a brush.
- Reinforce cracks by applying the reinforcing fleece IKO polyester Fleece 30 in the IKOpro Gutter Renovation layer and making sure the fleece is fully saturated.
- Rainproof at 20°C after 6 hours.

## Consumption rate:

+/- 0,6 L/m<sup>2</sup>

## Cleaning of tools:

IKO tech Cleaner

The technical information regarding the application of liquid waterproofing products supplied by IKO is provided in good faith on the basis of IKO's current know-how and experience, and assumes that these products will be used in accordance with the above-mentioned recommendations, under normal circumstances, and that these products were stored and handled in the correct manner. The above-mentioned information is only intended to inform the user about the various properties and/or recommendations, and can in no way be considered as a guarantee with regard to the merchantability and suitability for a specific purpose in view of the continuously changing environmental factors, including the specific conditions at the building site, the use of different materials and substrates, etc. As a result, and with the exception of binding legal stipulations to the contrary, IKO cannot be held liable on the basis of the provided information, and any other written recommendations and/or advice. Please contact IKO if you have any doubts regarding the processing, the end use or the application of these products. Users are recommended to consult the most recent edition of the technical data sheet. A copy of this will be provided upon request, or can be obtained from <https://eu.iko.com>.