

Roof&Wall Cleaner

Description:

Liquid and mildly acid cleaner that removes pollution and deposit of atmospheric origin on all types of substrates, like roofs and walls.

As efficient, for more than 90% based on natural raw materials and for more than 90% biodegradable.

Scrubbing or the use of a pressure washer is not required. The result is noticeable after just a few days.

The packaging is made of 100% recycled plastic.

Use:

IKO pro Roof&Wall Cleaner is used for: flat and pitched roofs (bitumen roof felt, slate-roofed, tiled, thatch, corrugated, ...); facades (bricks, concrete, plaster); terraces and garden furniture.

Caution is advised when the product is applied or splashed on certain types of powder coatings. First test the product on an invisible spot.

Given its acid nature, the cleaner can attack materials based on limestone.

Packaging:

Jerrycan of 5L (item number 02400405)

Storage:

2 years in the hermetically sealed packaging, when stored in a dry, cool and frost-free place.

Partly used containers may be resealed and used again after correct storage.

To avoid the risk of spillage, always store and transport in a secure upright position.

Colour:

Milky white

Technical characteristics:

pH 4,5



Application:

First remove large dirt accumulations manually for faster results.

Always shake the product before use.

Do not apply at ambient and substrate temperatures < 8°C and when rain is expected within 24 hours. Do not apply at high temperatures and in full sun.

Apply IKO pro Roof&Wall Cleaner undiluted on a dry or slightly damp substrate with a brush or sprayer.

Let IKO pro Roof&Wall Cleaner soak in, the cleaning will happen automatically.

Consumption rate:

From 5-10 m²/L, depending on the degree of dirt.

Cleaning of tools:

Water

Certificates:

Production ISO 9001 & 14001



The technical information regarding the application of liquid waterproofing products supplied by IKO is provided in good faith on the basis of IKO's current know-how and experience, and assumes that these products will be used in accordance with the above-mentioned recommendations, under normal circumstances, and provided that these products were stored and handled in the correct manner. The above-mentioned information is only intended to inform the user about the various properties and/or recommendations and can in no way be considered as a guarantee with regard to the merchantability and suitability for a specific purpose in view of the continuously changing environmental factors, including the specific conditions at the building site, the use of different materials and substrates, etc. As a result, and with the exception of binding legal stipulations to the contrary, IKO cannot be held liable on the basis of the provided information, and any other written recommendations and/or advice. Please contact IKO if you have any doubts regarding the processing, the end use or the application of these products. Users are recommended to consult the most recent edition of the technical data sheet. A copy of this will be provided upon request, or can be obtained from be.iko.com.