

# IKO tekband

## Description:

Prefabricated and self-adhesive bitumen-polymer tape

## Use:

- Sealing and closing joints or cracks to prevent water from infiltrating into the subgrade;
- Connecting and sealing joints to prevent the damaging of the bituminous mix and the appearance of cracks.
- Connecting and sealing coplanar road surfaces following repair and/or maintenance jobs such as joint repair between new and old surfaces following cabling operations or laying of sewers or technological systems;
- Jointing and connecting various parts, the edges of which form discontinuity on the road surface, between the bituminous mix and tram lines, concrete elements (such as kerbs and gutters), the outlines of functional elements such as manholes and drain covers.

## Characteristics:

Thickness	4mm
Meltingpoint	>130°C
Density at 25°C	+/- 1,34 kg/dm <sup>3</sup>
Flow at 60°C	0mm
Cone penetration at 25°C	22 0.1mm
Adhesion to concrete	76,2 +/- 5,5 N/cm <sup>2</sup>
Shore A hardness	70
Plasticity/impact strength	75% +/- 5%



## Implementation:

### Preparation of the joints

- The maximal size of repairable cracks must **not exceed 10 mm**.
- The surfaces involved must be perfectly dry, devoid of grease and free from dust or impurities.
- Installation must occur at air temperatures above 15 °C to enable it form a total seal by means of the traffic movement. At air temperatures lower than 15 °C prepare the surface with IKOpr Quick Primer Spray.

### 2. Application

- IKO tekband must be installed horizontally along the crack, equally divided across the sides of the crack.
- IKO tekband can be installed manually or with a trolley. The trolley will make installation easier and faster.
- The installation surface must be in an area of heavy traffic; Traffic movement is crucial for the product to work properly as it favours cracks compacting.
- The product will become bedded down though trafficking.

## Storage:

- We recommend using the product within 12 months.
- Store the product in a dry environment at a temperature between 5°C and 40°C.

## Sizing and palletization:

- 40mm wide and 25m length (item number 00015155)
  - 2 rolls per box
  - 54 boxes per pallet

The technical information regarding the application of liquid waterproofing products supplied by IKO is provided in good faith on the basis of IKO's current know-how and experience, and assumes that these products will be used in accordance with the above-mentioned recommendations, under normal circumstances, and that these products were stored and handled in the correct manner. The above-mentioned information is only intended to inform the user about the various properties and/or recommendations. and can in no way be considered as a guarantee with regard to the merchantability and suitability for a specific purpose in view of the continuously changing environmental factors, including the specific conditions at the building site, the use of different materials and substrates, etc. As a result, and with the exception of binding legal stipulations to the contrary, IKO cannot be held liable on the basis of the provided information, and any other written recommendations and/or advice. Please contact IKO if you have any doubts regarding the processing, the end use or the application of these products. Users are recommended to consult the most recent edition of the technical data sheet. A copy of this will be provided upon request, or can be obtained from <https://eu.iko.com>.