IKO fibral

Description:

Cellulose joint plate impregnated with bitumen.

Use:

Bottomplate for joints in concrete roads and for all joints being filled with bitumen compound.

Characteristics:

- Waterproof
- Rot resistant

Caracteristics:

Density	+/- 230 kg/m³
Compression	+/- 100 kPa
Thickness	10mm
Temperature resistance	Till 200°C



Implementation:

- The plate is put in place 2 cm under the surface of the concrete.
- The remaining 2 cm is filled with bitumen joint sealer.

Sizing and palletization:

- Straight plate - item number 00040050
  - Length: 2,5m
  - Height: 18cm
- Type A - item number 00040011
  - Length: 50cm
  - Height: 18cm
- Type C with cut-out - item number 00040023
  - Length: 50cm
  - Height: 18cm

The technical information regarding the application of liquid waterproofing products supplied by IKO is provided in good faith on the basis of IKO's current know-how and experience, and assumes that these products will be used in accordance with the above-mentioned recommendations, under normal circumstances, and that these products were stored and handled in the correct manner. The above-mentioned information is only intended to inform the user about the various properties and/or recommendations. and can in no way be considered as a guarantee with regard to the merchantability and suitability for a specific purpose in view of the continuously changing environmental factors, including the specific conditions at the building site, the use of different materials and substrates, etc. As a result, and with the exception of binding legal stipulations to the contrary, IKO cannot be held liable on the basis of the provided information, and any other written recommendations and/or advice. Please contact IKO if you have any doubts regarding the processing, the end use or the application of these products. Users are recommended to consult the most recent edition of the technical data sheet. A copy of this will be provided upon request, or can be obtained from https://eu.iko.com.