

IKO flexijoint

Description:

Extruded closed cell polyethylene foam

Use:

- IKO flexijoint is specifically developed for use in static and moving joints with different expansion forms (expansion joints, road joints,...)
- As joint filler, it helps to reduce amount of sealant used.
- Developed to be used with both hot melt compounds as with cold sealants like IKO hybritech Sealant.

Characteristics:

- Resistant to high temperatures.
- Remains separate from the joint filling compound or mastic.
- Allows the mastic to move freely and does not react chemically with it.

Characteristics:

Colour	White
Density at 20° C	+/- 30kg/m ³
Peak maximum temperature	+/- 180° C
Normal temperature	-40° C to 100° C
Compression of 500 N	70% crushing
Water absorption after 28 days	0,8 vol. % - doesn't absorb water
Resistance to chemicals	Chemically neutral foam

Implementation:

1. Preparation of the substrate

Repair the edges of the joint if necessary.

2. Application of IKO flexijoint

To allow the mastic to be applied without being repelled by the IKO flexijoint, use a nominal diameter of around 25% greater than the width of the joint.

Storage:

For an unlimited period in the original packaging.

Sizing and palletization:

- 6 mm diameter 1.500 r/m carton (item number 00015109)
- 8 mm diameter 900 r/m carton (item number 00015110)
- 10 mm diameter 1.700 r/m carton (item number 00015111)
- 13 mm diameter 1.100 r/m carton (item number 00015117)
- 15 mm diameter 780 r/m carton (item number 00015112)
- 25 mm diameter 280 r/m carton (item number 00015113)
- 32 mm diameter 190 r/m carton (item number 00015114)

The technical information regarding the application of liquid waterproofing products supplied by IKO is provided in good faith on the basis of IKO's current know-how and experience, and assumes that these products will be used in accordance with the above-mentioned recommendations, under normal circumstances, and that these products were stored and handled in the correct manner. The above-mentioned information is only intended to inform the user about the various properties and/or recommendations. and can in no way be considered as a guarantee with regard to the merchantability and suitability for a specific purpose in view of the continuously changing environmental factors, including the specific conditions at the building site, the use of different materials and substrates, etc. As a result, and with the exception of binding legal stipulations to the contrary, IKO cannot be held liable on the basis of the provided information, and any other written recommendations and/or advice. Please contact IKO if you have any doubts regarding the processing, the end use or the application of these products. Users are recommended to consult the most recent edition of the technical data sheet. A copy of this will be provided upon request, or can be obtained from <https://eu.iko.com>.