

IKO OECOPHALT R 0/4

Description:

Cold application reactive cold hydrocarbon. Solvent-free.

Use:

Final repair or resurfacing of concrete or hydrocarbon surfacing subjected to light, medium or heavy traffic.

Characteristics:

- Ready for use.
- Excellent adhesion.
- Immediate repair.
- Open for traffic immediately.
- IKO oecophalt retains high internal flexibility which contributes to its stabilisation.
- Usable below 0°C.

Characteristics:

- Colour: Black
- Size: 0/4 – closed texture

Consumption rate:

+/- 25 Kg/m² and per centimetre of thickness.

Cleaning tools and stains:

Immediately with solvent

Implementation:

Preparation of the support

- Cut out the degraded area to give it clean edges.
- Clean the surface using a wire brush.
- Remove water and mud.
- It is recommended to use IKO REACTIVE PRIMER SPRAY on the on the side.
- With concrete use always IKO REACTIVE PRIMER Spray on all the surface.

Applying IKO oecophalt

- IKO oecophalt is spread with a rake.
- Apply IKO oecophalt a little bit higher than the surface, spread some water on the product and mix to start the reaction.
- Level the product again.
- Compacted with a rammer or other suitable machine.
- Spread some water on the IKO oecophalt during the compaction.
- Open for traffic immediately.
- IKO Oecophalt has now limits of thickness.

IMPORTANT

- In case of low temperatures heat the surface, keep the product at room temperatures till pose.
- Calculate a little longer Harding time.

Storage:

- Storage cool and dry, do not store in open air.
- 6 months in hermetically sealed bags.

Packaging:

- Bags of 16 kg.
- 60 bags on 1 palette.
- Reactive primer spary 12 spray's per carton