

# IKO powerflex Stick grijs 6.0

**01560840**

## Description:

Waterproofing membrane composed of elastomer (SBS) bitumen with fire-retardant properties and a polyester-glass combination inlay. The upper surface is finished with light grey crushed slate and the lower surface is protected by a self-adhesive finition. This top layer can be applied for the finish of upstands.

## Installation

Installation: fully self-adhesive with IKOpro Activator.

The seams and joints must be welded with hot air.

Installation temperature (based on self-adhesive placement only)  $\geq 5^{\circ}\text{C}$ .

At temperatures  $\leq 10^{\circ}\text{C}$ . The rolls should be stored in a room  $\geq 10^{\circ}\text{C}$  before installation.

## Composition

Type of bitumen	Elastomeric
Upper surface finish	Light grey crushed slate
Inlay	Polyester-glass combination 180 g/m <sup>2</sup>
Lower surface finish	Self-adhesive bitumen with anti-stick film

## Technical characteristics:

Tensile strength L (EN 12311-1 MDV N/50 mm +/- 20%)	750
Tensile strength T (EN 12311-1 MDV N/50 mm +/- 20%)	500
Elongation L (EN 12311-1 MDV % +/- 15% abs.)	40
Elongation B (EN 12311-1 MDV % +/- 15% abs.)	40
Nail tear resistance(EN 12310-1 MDV N Only MF)	$\geq 150$
Flexibility at low temperature (EN 1109 MLV °C Surface/Bottom)	$\leq -20$
Flow temperature (EN 1110)	$\geq 110$
Shear resistance (EN 12317-1 MDV N/50 mm)	$\geq 500$
Dimensional stability (EN 1107-1 MLV)	$\leq 0.3$
Fire resistance	Broof(t1)
Vapour diffusion resistance ( $\mu\text{d}$ )	NPD
Root resistant (EN 13948)	-

## Sizing and palletization:

Nominal thickness (mm)	3,0
Thickness tolerance (mm)	+/- 0,2
Length (m)	6
Width (m)	1
Width of overlap (cm)	10,0
Weight per roll(kg)	+/- 26
Number of rolls / pallet	30
Type of pallet	1 X 1,2 m single use

**Always use a suitable pallet hoisting hook for vertical transport.**

## Certificates:

- CTG 499
- Production ISO 9001 & 14001

IKO hereby certifies that this construction product complies with the provisions of the following European Directive(s) if installed in accordance with the system directions and installation rules set out in the documentation:

- Council Directive 89/106/EEC on Construction Products
- EN 13707

FPC certificate obtained from SGS Notified Body, registered under registration number 0958.

Certificate number: 0958-CPR-2009/1.

